Performance



Parts List	
Exhaust Canister Assembly	1
Heat Shield	1
Hardware	
1/4-20x3/8" SS Button Head Screws	2

ATTENTION: We strongly recommend that this product is installed by a qualified motorcycle mechanic. If you have any doubts as to your ability to perform this installation, please consult with a dealer or repair shop. Be sure to read all instructions before starting installation. Be sure the motorcycle is secure and stable throughout the entire installation.

Installation Instructions

- 1. Remove the factory muffler, following the instructions in your model specific factory manual. Some of the parts and hardware will be re-used for installation.
- 2. Remove the exhaust valve servo.
- 3. Remove the cables from the exhaust valve servo.
- 4. Re-install the servo, connecting the wire plugs. (Do not re-install the cables)
- 5. Remove the heat shield from the Toce Double Down pipe.
- 6. Install the new pipe using your stock hardware.
- 7. Re-install the heat shield.

This installation is complete and you are ready to ride!



Thank you for your purchase!

If you need further assistance please check out our Facebook or YouTube channel for video instructions. Or call us directly at the number listed above. We hope you follow us on Instagram, like us on Facebook or leave a review: we would love to hear your feedback.

Warranty

Toce Brothers Performance products are intended for closed course competition and show use only, and therefore are sold "as is" without warranty. Toce Brothers Performance, LLC specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products.