



Parts List	
Exhaust Canister Assembly	1
Satin Finish SS Mid-Pipe (Optional Black)	1
Hardware	
T-Bolt Clamp	1
Springs	2
1/4-20c 1-1/4" SS Hex Mounting Bolts	2
Drop Down Hardware	

ATTENTION: We strongly recommend that this product is installed by a qualified motorcycle mechanic. If you have any doubts as to your ability to perform this installation, please consult with a dealer or repair shop. Be sure to read all instructions before starting installation. Be sure the motorcycle is secure and stable throughout the entire installation.

#### Installation Instructions

- 1. Remove the factory muffler, following the instructions in your model specific factory manual. Some of the parts and hardware will be re-used for installation.
- 2. Slide the clamp onto the front end of the mid pipe.
- 3. Slip the mid-pipe onto the factory header pipe.
- 4. Align the canister and install the new upper mounting bolts. Do not tighten at this time.
- 5. Once all parts are installed, step behind the bike and check alignment. Make any necessary adjustments by moving the mid-pipe left or right to center the exhaust can. When the can is centered, tighten the upper mounting bolts then tighten the t-bolt clamp on the mid-pipe.
- 6. Install the retention springs.

# You're finished! Enjoy!

# Thank you for your purchase!

If you need further assistance please check out our Facebook or YouTube channel for video instructions. Or call us directly at the number listed above. We hope you follow us on Instagram, like us on Facebook or leave a review: we would love to hear your feedback.

#### **BAFFLE CORE REMOVAL**

- 1. Remove the 1/4-20 locking hex nuts from the front of the canister.
- 2. Tap on the studs with a plastic hammer to drive the baffles out. You may need to use a small screwdriver or rod to completely remove the baffles. Be careful not to scratch the inside of the pipes while removing.
- \*Baffles may be removed for repacking and reinstalled.
- \*\*We do not recommend operating your motorcycle with baffles removed.

### Warranty

Toce Brothers Performance products are intended for closed course competition and show use only, and therefore are sold "as is" without warranty. Toce Brothers Performance, LLC specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products.